

CLIMAX MINE TAILINGS DISCLOSURE REPORT

AUGUST 2025

Table of Contents

Introduction.....	3
Summary of FCX's Approach to Tailings Management.....	3
Evolution of FCX's Tailings Management System and Implementation of the Tailings Standard.....	3
1.0 Our TMS.....	4
1.1 TSF Lifecycle	5
1.2 Governance Framework	6
1.3 Risk Informed Decision Making	8
1.3.1 TSF Risk Assessment and Consequence Classification	8
1.3.2 Risk Management	9
1.3.3 Surveillance and Review.....	10
1.4 Approach to TSF Safety Performance Reviews.....	10
2.0 Climax TSFs	11
2.1 Description of the Climax Mine, Mill and TSF Areas.....	11
2.2 Tailings Facility Design	14
2.3 Risk Assessment, Impact Assessment, and Consequence Classification.....	15
2.4 ERP.....	16
2.5 Dates of Most Recent and Next Independent Reviews.....	16
2.6 Material Findings from TSF Safety Performance Reviews of the Climax TSFs and Mitigations to Reach ALARP	17
2.7 Material Findings of Annual Performance Review of Environmental and Social Monitoring Programs	18
2.8 Confirmation of Adequate Financial Capacity	18
CAUTIONARY STATEMENT	19
Appendix: Consequence of Failure Classification Flowchart for Population at Risk.....	20
Other Metrics.....	21
Likelihood Categorization	22
ANNEX 1: Acronym Definitions.....	23

Introduction

Freeport-McMoRan Inc. (FCX) is committed to transparency by ensuring relevant information regarding Tailings Storage Facilities (TSFs) at our operations is readily available through public disclosures and active engagement with stakeholders.

This report supports our efforts to publish and regularly update information on TSF management, implementation of our tailings governance framework, our policies, standards and approaches to the planning, design, construction, operation, monitoring, maintenance, closure and post-closure of tailings facilities in alignment with the Global Industry Standard on Tailings Management (Tailings Standard)¹ Requirement 15.1. It also supports our commitment to publish and update, at minimum annually, information on the TSFs at the Climax Mine in Colorado in alignment with Tailings Standard Requirement 15.1B.

Summary of FCX's Approach to Tailings Management

Effective and responsible tailings management is critical to mining safely, protecting people and the environment and maintaining social license to operate. We strive to continuously manage, enhance and innovate our tailings system in a manner that minimizes impacts to stakeholders and the environment. We recognize the potential failure of a TSF at any of our mining operations could cause severe or catastrophic damage that could result in loss of life, property damage, or environmental harm. Using appropriate management approaches and technologies, we operate with a bias for action by aiming to quickly identify and address issues at our TSFs.

The health and safety of our workforce and communities, and the protection of the environment are fundamental to our extensive tailings management system programs and approach. Our objective is to have zero fatalities, zero catastrophic failures, and zero unplanned discharges from any of our TSFs.

Our **Tailings Management Policy** outlines our continued commitment to managing our tailings responsibly and effectively across our sites globally. This policy is designed to be implemented in conjunction with our **Environmental**, **Human Rights**, and **Social Performance** policies and associated management systems. Additionally, we are committed to implementing the Tailings Standard at applicable TSFs in the Americas.

Evolution of FCX's Tailings Management System and Implementation of the Tailings Standard

FCX's comprehensive Tailings Management System (TMS) has evolved over more than 20 years and is applied at all TSFs in the Americas over their entire lifecycles. This system incorporates applicable regulations and international best practices, including the integration of the Tailings Standard. Through the TMS, we promote continuous improvement at our TSFs. We systematically analyze potential failure modes, then work to eliminate or mitigate them to minimize the risk of failure scenarios associated with our TSFs. For closed sites where no material risks remain, a "safe closure" designation is assigned, as described in Section 1.1.

FCX's TSFs are designed and managed throughout their lifecycles using Risk Informed Decision Making (RIDM) with precautionary or performance-based design approaches identified by each site's Engineer of Record (EoR) along with detailed inspections by the FCX Tailings Stewardship Team (TST) third-party reviewers, and reviews by the Independent Tailings Review Board (ITRB). Our sites' EoRs design new TSFs and analyze existing TSFs using the stringent criteria for earthquakes and floods, applicable to Extreme TSFs, regardless of actual consequence.

¹ The Tailings Standard was established by the International Council on Mining and Metals (ICMM), the United Nations Environment Program, and Principles for Responsible Investment.

In accordance with the Tailings Standard, FCX's updated consequence classification approach incorporates each TSF's detailed information and analysis that has been enhanced over the past few years to reduce uncertainties and incorporate expert opinions on thresholds for Credible Failure Modes (CFMs). Our approach is derived from the Tailings Standard, and we take a conservative approach to consequences where there is a potential Population at Risk (see Section 1.3 and the Appendix for more information). FCX's subsidiaries evaluated consequence classifications based on this updated approach, beginning with TSFs that were previously classified as Extreme or Very High based on hypothetical failure.

In line with RIDM, we continue to conduct additional investigations, analyses, and, when necessary, enhancements of our controls or take additional actions to reduce residual risks to as low as reasonably practicable. In doing this work, we have reduced our uncertainties and increased our confidence in understanding our TSFs.

Monitoring our TSFs and striving to minimize potential risks is an ongoing process, and our disclosures will be updated as required by the Tailings Standard.

1.0 Our TMS

FCX has comprehensive measures in place to help ensure our TSFs are designed, built, operated, closed, and monitored/maintained to minimize risk to our workforce, communities, and the environment.

The TMS comprises specific programs to address aspects of tailings planning, design, operation, maintenance, surveillance, and risk management over the TSF lifecycle. Although there is some overlap among the categories, our safeguards generally fall within four categories:

1. Engineering practices and safe designs

- We have robust stage-gate processes for engineering and design; our technical experts either manage or are embedded in projects to enhance shared knowledge and consistency in rigor and quality. In collaboration with the EoR, we conduct extensive site investigations and detailed site characterization to inform state-of-practice (or leading practice) engineering analyses and build a comprehensive knowledge base. Our EoRs design new TSFs and analyze existing TSFs using the stringent criteria for earthquakes and floods, applicable to Extreme TSFs, regardless of actual consequence.

2. Adherence to construction and operational parameters through monitoring and use of technology

- Our programs for operations, maintenance, inspections, and monitoring incorporate on-the-ground, automatically collected, and remote sensing data to enable regular analysis and internal reporting. Monitoring results are compared to established performance criteria. Action plans are developed and tracked to completion to help verify the TSF is operated in accordance with the design intent. Our Early Indicator Dashboard provides a mechanism to communicate performance in a timely manner to appropriate stakeholders at our sites and with our corporate leadership.

3. Multi-tiered oversight and management of change

- Our TMS includes mechanisms for internal and external reviews, including reviews by internal subject matter experts, Responsible Tailings Facility Engineers (RTFEs), EoRs, the TST, and ITRBs. See sections 1.2 and 1.4 for more information. Reporting on monitoring program results and findings from these reviews are distributed to site and corporate leadership, including the Accountable Executive (AE), to inform and drive our bias for action.
- We use a formalized management of change process to assess, control, and communicate changes that range from minor to material, as well as to handle temporary and permanent changes.

4. Adherence to practices grounded in continuous improvement and learning from past experiences, including industry failures and best practices

- We actively participate in industry technical conferences and research initiatives, apply lessons from case histories, and conduct regular operator and engineer education and training.

Our RIDM process is an example that spans all four categories of safeguards and is discussed further in Section 1.3.

Figure 1 shows the evolution of the FCX TMS and key programs that exemplify the categories discussed above.

COMMITMENT TO SAFETY - NO FAILURES




Figure 1. Tailings Stewardship & Management: A 20-Year Evolution.

1.1 TSF Lifecycle

A TSF lifecycle includes the design, construction, operation, closure, and post-closure phases. A TSF undergoes continual changes over its lifecycle, and these changes should be considered and managed to maintain safety and structural integrity. FCX works closely with internal and external experts, including the EoR, TST, ITRB, and TMS Implementation Assessor, for management across the full lifecycle of the TSF.

FCX provides the “Status” of our TSFs in our public disclosures as follows:


- **Development** - TSFs that have completed permitting and are in stages of design and / or construction through commissioning, prior to start of tailings deposition.
- **Active** - TSFs with tailings distribution infrastructure in place for the intent of raising dam crest.
- **Inactive** - TSFs that are not intended to receive tailings deposition in the current operating plan but have not yet implemented final closure activities.
- **Closed** - TSFs that are no longer in operation and have been closed to meet applicable regulatory requirements, but for which safe closure under the Tailings Standard is not yet complete or confirmed.
- **Safely Closed** - TSFs that, upon collection and evaluation of additional data, have reached “Safe Closure” status as defined by the Tailings Standard; to receive this designation, TSFs require confirmation by an ITRB and AE. A Safely Closed TSF does not pose ongoing material risk to people or the environment.

1.2 Governance Framework

We believe our programs and safeguards are effectively implemented through the promotion of open and ongoing communication throughout our organization and a bias for action.

We remain focused on the safe execution of our TMS by maintaining robust, multi-tiered governance of our tailings programs, which involves appropriately qualified personnel with clearly defined roles, responsibilities, and accountabilities. There are multiple layers of assurance we apply to all TSFs: site-level implementation, functional accountability, third-party review, and board and executive leadership oversight as shown on Figure 2 and described as follows.

Active Sites^{*}



^{*} Sites with only Inactive and / or Closed TSFs utilize a parallel structure reporting through the Chief Sustainability Officer.

^{**} In some cases, the General Manager may report to a Division Vice President or President who in turn reports to the COO-President Americas.

Figure 2. Organizational Structure for Tailings Management System Collaboration, Engagement, and Review (Active Sites).

Brief description of key roles in FCX's governance structure

1. Site-Level Implementation

- **Site Tailings Management, Engineers, and Operators:** Internal team that implements the tailings management system and regularly monitors, identifies, and addresses potential risks.
- **Responsible Tailings Facility Engineer (RTFE):** Internal engineer appointed by the AE responsible for the integrity of assigned TSFs. The RTFE provides technical expertise, manages risk, and liaises with the EoR. Corporate discipline experts provide regular support to RTFEs.
- **Engineer of Record (EoR):** External engineer who provides expert design and engineering analysis, technical support, inspection, review, and guidance to support an RTFE in achieving design intent of their assigned TSF.

2. Functional Accountability and Responsibilities

- **Accountable Executive (AE):** Chief Operating Officer (sites with active tailings operations) or Chief Sustainability Officer (sites without active tailings operations) who reports to the FCX Chief Executive Officer and is accountable for the safe management of TSFs and for minimizing the social and environmental consequences of any TSF failure.
- **Tailings and Water Director:** Oversees the RTFE's activities and has delegated responsibilities from the AE for engaging with and reviewing the site-level implementation of TMS activities.

3. Third-Party Review

- **Independent Tailings Review Board (ITRB):** Third-party, internationally known expert panels who provide independent opinions and guidance on the physical integrity, safety, and performance of TSFs and have access to corporate senior leadership. Members have decades of experience in applicable disciplines.
- **Tailings Stewardship Team (TST):** Third-party professional engineers who have not been directly involved with the design or operation of the TSFs and internal experts who inspect all TSFs, review documents and monitoring data, identify potential deficiencies, and recommend corrective actions.
- **Tailings Management System (TMS) Implementation Assessment:** External consultant with sufficient knowledge and understanding of the TMS to assess the efficacy of the TMS applied at a site-specific level, including key tasks, roles and responsibilities, and associated governance structure to support proper management and operation for maintaining TSF structural integrity.

4. Board and Executive Leadership Oversight

- **Corporate Senior Leadership:** Executive leadership that participates in major decisions related to the tailings management program, including allocation of resources for TSF-related operations, initiatives, and projects.
- **Board of Directors:** Corporate governing body firmly committed to providing active oversight and, with the Corporate Senior Leadership, the necessary financial and technical resources to maintain the safety and integrity of our tailings facilities globally, with a focus on risk management and continuous improvement. The AE regularly reports to the Corporate Responsibility Committee of the Board of Directors on matters related to the tailings management, including implementation of the Tailings Standard.

1.3 Risk Informed Decision Making

Risk is a combination of the potential consequences of an event and the probability, or likelihood, of that event occurring.

FCX applies RIDM throughout the full lifecycle of each TSF from design to post-closure. RIDM allows us to make informed decisions while linking the stability performance and risk level that is acceptable for a TSF; the process includes periodic updates, so that changes in the operation and/or performance, which may alter the risk profile of a TSF, can be considered.

As part of FCX's TMS, RIDM consists of three primary elements:

1. Risk Assessment
2. Risk Management
3. Surveillance and Review

1.3.1 TSF Risk Assessment and Consequence Classification

TSF risk assessments include risk identification, analysis, and evaluation used to determine which measures are, or should be, in place to eliminate or minimize risk. Outcomes also inform TSF consequence classification.

The risk assessment focuses on potential physical failures of each TSF, which may include instability, slope failures, excessive slope erosion, overtopping of the impoundment, and internal erosion. For the purposes of the assessment, FCX defines a TSF failure as the unintended loss of the structural containment where the tailings and water released could be impactful.

Other risks related to TSFs include, but are not limited to, occupational health and safety, environmental, social, economic, value chain, and other potential long-term sustainability and business risks. These risks are documented in the site's sustainability risk register process; see the [FCX Annual Report on Sustainability](#) for more information.

The TSF risk assessment is updated with our full stakeholder group and workshop process every three years for applicable TSFs, and approximately every six years for Safely Closed TSFs. In the interim, the risk assessment is reviewed annually by the RTFE, site engineering staff, and the EoR.

During the risk identification and analysis workshops, multidisciplinary teams including the EoR, RTFE and internal team members and additional external experts as appropriate, use available information such as TSF-specific detailed data and engineering analysis, experience from team members, case histories, and regulatory data to identify a specific chain of events that could lead to a TSF failure. The group analyzes how a failure may occur, what factors exist that make the potentially credible failure modes more or less likely (considering the site-specific knowledge base, existing robust controls and uncertainties), and ultimately determine which are credible failure scenarios.

Risk analysis leads to an understanding of each credible failure scenario for a TSF; a scenario comprises a CFM and an associated consequence that is technically feasible considering analysis and expert opinion on a minimum threshold of possibility of occurrence during a structured analysis process. To determine whether a failure mode and an associated scenario are credible, workshop participants use tools such as semi quantitative risk analysis to estimate the likelihood of occurrence of each potentially credible failure mode, the likelihood of an adverse structural response, and the magnitude of potential adverse consequences. The group's best-estimate conservative ranking is used for the likelihood categorization of each CFM guided by information described in the Appendix.

CFMs reflect the residual uncertainty that exists around physical conditions and controls in the TSF considering all site-specific information and analyses. The resulting consequence classification is not an indication that a credible failure scenario will occur and having CFMs is not a reflection of TSF safety.

The credible failure scenarios are then used to create a TSF consequence classification, as defined by the Tailings Standard. The TSF consequence classification is based on downstream conditions and potential impacts of CFMs, including incremental losses to Populations at Risk, environmental impacts, health/social/cultural impacts, and infrastructure and economic impacts.

FCX integrates our value of safety into our tailings programs by taking a conservative approach to consequence classification (see Appendix for additional detail). Our definitions for consequence classification align with the Tailings Standard except as outlined below.

- If there is at least one permanently situated person at risk (permanent Population at Risk) – including the public, employees, or contractors – the CFM is classified as Extreme. Whereas the Tailings Standard requires a Population at Risk (see Appendix) greater than 1,000 people to be classified as Extreme.
- If there is no permanent Population at Risk, but there is a transient Population at Risk (see Appendix), the minimum consequence classification is Significant.
- Other metrics (as defined in the Tailings Standard for environmental and health; social and culture; and infrastructure and economics) help further determine the consequence classification (see Appendix).

Appropriate modeling of credible failure breach flow or slump runout scenarios is used to inform our understanding of potential consequences. In accordance with the Tailings Standard, we assign a TSF a consequence classification based on the highest consequence categorization of CFMs for that TSF. The consequence classification is primarily used for communications and disclosure purposes. The TSF consequence classification is formally revisited when the Risk Assessment is updated.

Regardless of the TSF consequence classification, all of FCX's operating TSFs and Development TSFs are designed, analyzed, and operated using Extreme loading criteria. Design criteria for Inactive, Closed, and Safely Closed TSFs are informed by the Extreme loading criteria and assigned using the as low as reasonably practicable (ALARP) principle.

A risk assessment compares the outcomes of the risk analysis for existing conditions to determine if risks are within acceptable limits, whether existing risk reduction measures and controls are adequate, and what additional risk reduction measures should be considered (pursuant to the ICMM Tailings Management Good Practice Guide updated in 2025). The risk of each CFM is reviewed following the ALARP principle. In some cases, the ALARP principle may not be satisfied, and further risk reduction measures to reduce the likelihood of occurrence or the potential adverse consequences may be required.

1.3.2 Risk Management

Based on learnings from the TSF risk assessment, our expert teams use engineering and operational controls to prevent, minimize, and / or mitigate risks to meet the ALARP principle. These controls include an ongoing focus on quality engineering design, construction, and operating discipline. Controls could include a buttress or other mitigating construction activity (e.g., foundation improvements or stormwater management enhancements). Additionally, part of managing risk is engaging with our communities and external authorities to maintain a shared state of readiness through robust emergency preparedness and response planning for credible failure scenarios.

The risk assessment steps are repeated until the risk conforms to the ALARP principle and is followed by annual reviews and periodic TSF risk assessment updates.

1.3.3 Surveillance and Review

Surveillance and review in our RIDM program include activities as outlined in our Operations, Maintenance and Surveillance (OMS) Manual. Surveillance involves inspection and monitoring of the operation, structural integrity, and safety of the TSF. It consists of both qualitative and quantitative comparison of actual to expected behavior and its activities are performed by appropriately trained personnel. Review of surveillance information occurs throughout the year for each TSF and is facilitated via internal reporting.

1.4 Approach to TSF Safety Performance Reviews

The TMS programs and their results are reviewed and evaluated for effectiveness regularly as part of routine operations and in focused performance reviews.

Internal and external reviews enhance confidence in safe tailings management, helping to confirm each TSF is performing in accordance with the design intent and to support informed decision making.

The following multifaceted review mechanisms are in accordance with the ICMM Tailings Management Good Practice Guide and satisfy the requirements of the Tailings Standard.

- **Annual Performance Review:** Each year, all TMS activities are reviewed to evaluate overall TSF performance and documented to serve as a record of tailings analyses, design, construction, inspections, and monitoring results from the preceding year with references to supporting documentation. The review summarizes key findings and assesses the cumulative impact of activities and changes to the TSF.

The EoR provides an overall conclusion about the performance of each TSF and provides recommendations if deviances from the design intent or good practice are found. Opportunities are identified to improve or optimize TSF performance or other TMS activities. Where material changes have occurred, recommendations are made to update the design basis, performance objectives and monitoring criteria, or other OMS activities as relevant. Actions taken to address recommendations not resolved by the end of the previous reporting period are summarized in the following year's annual performance review.

- **TST Inspection:** This inspection is a review of TSFs and supporting infrastructure with a focus on TSF safety. The TST inspects all TSFs, identifies potentially significant deficiencies, recommends corrective actions, and reviews whether recommended actions were completed through acceptable measures. The TST performs annual inspections of all Active TSFs. Inspections of Inactive / Closed TSFs occur every one to three years, depending on risk profile, status of ongoing care and maintenance programs, and progress towards safe closure.
- **ITRB Review:** The ITRB is comprised of a group of third-party experts that independently reviews and assesses design, construction, and tailings management practices for the applicable Americas TSFs. The ITRB holds periodic meetings as often as bi-annually, but no less frequently than quadrennially, for TSFs that are not Safely Closed. The ITRB meets at least every six years for Safely Closed TSFs. ITRBs review information from significant field investigations and geotechnical and hydrotechnical analyses, material maintenance activities or repairs, progress on recommendations, and otherwise provide input on technical or operational issues. The RTFE and site team work collaboratively with the EoR to develop an action plan to address each recommendation.
- **TMS Implementation Assessment:** This periodic review typically occurs approximately every four to six years, depending on several factors, and is conducted to assess the efficacy of the TMS applied at a site-specific level, including key tasks, roles and responsibilities, and associated governance structures to support proper management and operation for maintaining TSF structural integrity. The RTFE and site team develop action plans and schedules to incorporate the recommendations.

For disclosure purposes, a material finding for a TSF Safety Performance Review means that the finding would result in:

- A significant update to the TSF design and / or design criteria, operations, or monitoring system; and / or
- Activation of the Emergency Preparedness and Response Plan (EPRP) or Emergency Response Plan (ERP).

In addition to review processes with the EoR and independent reviewers, regulatory or permit-driven reviews are defined based on site- and TSF-specific factors.

2.0 Climax TSFs

This report presents a summary of the 2024 Annual Performance Review and other pertinent information for the TSFs at the Climax Mine. The reporting period is January 1, 2024, to December 31, 2024, unless otherwise noted. This summary provides information per Tailings Standard Requirement 15.1.

2.1 Description of the Climax Mine, Mill and TSF Areas

This section provides a description of the Climax operations, including general background on the site, history of the mining and milling operations, and details on the TSFs.

Development of the Climax molybdenum ore body began in the early 1900s. Historically, ore had been mined using the underground block-caving method; however, more recently, ore has been mined using an open pit method. The Climax mining complex is owned and operated by the Climax Molybdenum Company, an indirect, wholly owned subsidiary of FCX. Technical services and support to the Climax Mine, including the TSFs, is provided by corporate employees of FCX.

The Climax Mine site is located in a mountainous region on the continental divide, with the highest bench elevation at approximately 4,050 meters above sea level. This region experiences significant snowfall during the winter months and develops a snowpack that typically peaks in depth just before spring runoff. Summer precipitation is influenced by the North America monsoon. This region of Colorado is characterized by a low to moderate level of seismicity, with a lack of large historical earthquakes. The seismic hazard at the mill site is affected by the Mosquito Fault, which passes through the Climax open pit and to the east of the TSFs.

Climax has three individual TSFs – Robinson, Tenmile and Mayflower. The TSFs are impounded by four tailings embankments – 1-Dam, 2-Dam, 3-Dam, and 5-Dam. Of the three TSFs, two are currently active and able to receive additional tailings, while one facility is closed. After removal of molybdenum from mined ores, tailings are transported northeast of the mine/mill and placed in the Climax TSFs. Tailings are deposited into the Climax TSFs as a slurry, using header and spigot upstream deposition methods. Pumping systems are used to return the supernatant process water from the TSFs to the milling circuit for reuse. Water is naturally attenuated in the system on an annual cycle, with treatment and discharge offsite to maintain a neutral water balance.

The Climax TSFs are located in the Tenmile Creek drainage, adjacent to the Tenmile Range of the Rocky Mountains. The surface geology in the Tenmile Creek drainage is dominated by glacial sedimentary deposits underlain by sedimentary complexes (Maroon and Minturn Formations) and intruded by igneous porphyries.

The Climax TSFs are located to the north of the mill area and open pit, and to the west of Highway 91 at locations listed in Table 1. Figure 3 shows the general layout of the Climax Mine, which generally includes the mill area, open pit, Robinson Lake, and the three TSFs.

Table 1. Climax TSFs*

Name	Location	Status*	Description
Mayflower TSF	39° 26' 2.28" N 106° 10' 46.45" W	Active	The Mayflower TSF is impounded by 5-Dam, an upstream- constructed sand embankment. Deposition at the Mayflower TSF began in the 1970s, with initial deposition consisting of underflow sand drainage system. Mayflower TSF received tailings until the 1980s when the mine site temporarily shut down. Tailings deposition resumed in 2014. Mayflower is currently the primary tailings depository for the Climax site.
Tenmile TSF	39° 24' 31.75" N 106° 11' 40.54" W	Active	The Tenmile TSF is impounded by 3-Dam, an upstream-constructed sand embankment. Deposition at the Tenmile TSF began in the 1950s and received tailings until the 1980s when the mine site temporarily shut down. Tailings deposition resumed when the mine restarted in 2012 and has been intermittent.
Robinson TSF	39° 23' 59.19" N 106° 12' 3.88" W	Closed	The Robinson TSF is impounded by 1-Dam and 2-Dam, both upstream-constructed sand embankments. The 2-Dam embankment has been buttressed by tailings as the Tenmile TSF impoundment has risen over time. Deposition at the Robinson TSF began in the 1930's. Deposition ceased in the 1970s. Robinson TSF is currently closed and reclamation activities, including regrading and placement of a cover layer, have occurred. Additional improvements are planned for the future.

* See Section 1.1 for description of "Status."



Figure 3. General Climax Mine Layout (Imagery from October 2024).

2.2 Tailings Facility Design

This section presents a summary of the design for the Climax TSFs, including construction means and methods through the TSF lifecycle. The Climax TSF designs are informed by assessment of TSF potential risk, site conditions, water management, mine plan operations, social and environmental impact studies, economic feasibility, and geotechnical evaluations. The design and operation of the Climax TSFs are regularly reassessed when appropriate and updated to reduce risk and increase robustness. The updates are based on informed decisions accomplished through the regularly scheduled enhancements to instrumentation and geotechnical investigation data, regular inspections, instrumentation and operational monitoring, and geotechnical performance evaluations.

The Climax TSF designs and analyses are conducted by the site's EoR. Based on available documents, the EoR's company and its predecessors have been involved with supporting the Climax TSFs since the 1960s.

The Climax TSFs were designed to be constructed using the upstream raise method. The starter dams for the initial TSFs generally were composed of compacted locally available construction materials. Operational raises were completed using traditional header and spigot whole tailings upstream deposition. This method of construction has continued throughout the life of the Climax TSFs. The upstream method results in a relatively coarse free-draining sand shell with fine-grained tailings deposited into the impoundment.

The initial Climax TSF designs included embankment slopes as steep as 2 horizontal (H) to 1 vertical (V). However, as the TSFs were operated, the designs were modified to include shallower slopes. As the state of practice in geotechnical engineering has advanced over the years, increasingly detailed investigations and analyses have been completed by the EoR resulting in changes in design criteria and design. The current design includes:

- Limited raise rates (rate at which tailings are deposited on TSF).
- Moderate overall downstream slopes of 4H to 1V (3-Dam and 5-Dam) and 4.6H to 1V (1-Dam) that enhance stability of the TSFs.
- Conservative material behavior assessment of the structural zone and foundation materials, and the pore pressure characterization of the tailings material in the structural zone.
- Foundation drainage systems that promote downward drainage through the embankment and seepage transport to collection systems below the TSF. Horizontal drains have been installed as needed to supplement the foundation drainage systems. Waters draining to the seepage collection systems are pumped into the TSF ponds, where they rejoin the process water circuit. The reclaim process water is generally recycled back to the mill, though some of the process water is treated and released downstream into Tenmile Creek.

As described in Section 1, the Climax TSFs are actively monitored for performance and periodically re-evaluated for stability.

The closure strategy includes the following concepts:

- The general closure concept for the Climax TSFs includes reclamation of the TSFs with a cover system that limits net infiltration and a soil matrix that supports establishment of vegetation to mimic the natural local ecosystem and contains diversion channels that convey snow melt and storm water off the top surface.
- The TSFs' embankment faces will remain at the same downstream slope as the active facilities (varies from 4H:1V to 4.6H:1V).
- Storms up to the Probable Maximum Flood (PMF) will be routed off the TSFs with the intent to minimize net infiltration on the reclaimed surface. Long-term seepage will be addressed by continued management of seepage throughout the draw down period.

Select design information for the Climax TSFs is included in Table 2.

Table 2. Select Design Information for the Climax TSFs as of December 31, 2024

	Mayflower TSF	Tenmile TSF	Robinson TSF
Primary Construction Material	Tailings		
Construction Method	Upstream		
Tailings Embankment Downstream Slope (H:V)	4:1 or shallower	4:1 or shallower	4.6:1 or shallower
Embankment Height (crest to downstream toe in meters)	83	125	67
Stored Tailings (million metric tons)	95	190	170
Permitted Capacity (million metric tons)	266	193	170
Inflow Design Flood ²	PMF		
Safety Evaluation Earthquake	1/10,000-year annual exceedance probability		

2.3 Risk Assessment, Impact Assessment, and Consequence Classification

This section provides a summary of risk assessment findings for the Climax TSFs, consequence classifications, and a summary of impact assessments and human exposure and vulnerability to credible failure scenarios.

In accordance with ICMM and the Tailings Standard, a comprehensive risk assessment for the Climax TSFs was completed in June 2024 and presented to the ITRB. A review and update of the risk assessment occurred later in October 2024. Our risk assessment process is described in Section 1.3.1.

Using information collected over the life of the Climax TSFs, a multi-disciplinary stakeholder group – including the RTFE, EoR, and other internal stakeholders – led by an expert risk assessment facilitator, initially identified 103 potentially credible failure modes related to the Climax TSFs through a series of semiquantitative risk analysis workshops.

Extensive engineering, monitoring and instrumentation, operational practices, analyses (geotechnical and hydrotechnical), field investigation and laboratory test data were reviewed and utilized to analyze each potentially credible failure mode, understand how the potential failure may occur, what factors exist that make the potential failure mode more or less likely to occur, and analyze and determine which are CFMs. Ultimately, the group determined that there is one CFM for the Climax TSFs.

² “Probable Maximum Precipitation” (PMP) or “Probable Maximum Flood” (PMF) are terms often used to denote extreme hydrological events. The Climax TSFs’ available capacity exceeds the required capacity of “Extreme” external flood design criteria referenced in the Tailings Standard and applicable regulations. FCX considered the potential impacts of climate change when evaluating robustness of designs.

Further analysis was completed to determine the potential impact of the CFM and the consequence classification of the TSFs. As summarized in Table 3, the Robinson TSF is classified as “Significant Consequence” based on a slump runout analysis and evaluation of the CFM’s potential impacts. The Mayflower TSF and Tenmile TSF do not have a corresponding classification as they have no CFMs. See the Appendix for the consequence classification flowchart and matrix as well as the likelihood categorization matrix.

Table 3. Credible Failure Scenarios (Modes and Consequences) as of December 2024

TSF	Credible Failure Scenario	Likelihood	Consequence	Potential Impact
Mayflower	None	N/A	N/A	No credible failure scenarios
Tenmile	None	N/A	N/A	No credible failure scenarios
Robinson	Earthquake causes weakening of embankment or foundation materials and leads to failure at 1-Dam	Moderate	Significant	Transient (see Appendix) personnel infrequently at risk

The risk assessment considered whether there are any measures needed to minimize risk to ALARP. The risk of each CFM was evaluated following the ALARP principle. Resulting actions are summarized in Section 2.6.

Potential consequences in the event of a CFM were informed by a slump runout model; the assessment of potential human exposure and vulnerability was most recently updated in October 2024. The term Personnel used in the table above refers to infrequently present Climax employees and contractors working on the Robinson TSF.

We aim to update this assessment when there is a material change to the Climax TSFs or an update to the knowledge base, including the social and economic context characterized by the social baseline study.

2.4 ERP

The Emergency Response Plan (ERP) was updated in 2024, and additional updates are planned for 2025. The 2024 update was developed using the CFM in Table 3 and associated slump runout analysis where applicable. The risk assessment did not identify CFMs at the Climax TSFs that could have off-site impacts and therefore do not require a separate EPRP, which would be co-developed with local emergency management agencies and the broader community.

The ERP is reviewed annually and is informed by the Climax TSFs risk assessment, which is reviewed annually and updated triennially. Appropriate personnel were trained on the ERP in early 2025 and participated in a tabletop exercise in 2022. Another tabletop exercise related to a tailings scenario is planned for later in 2025.

2.5 Dates of Most Recent and Next Independent Reviews

Per Climax’s OMS manual, its internal site engineers performed routine inspections during the reporting period. The RTFE and multiple levels of internal leadership, as well as the EoR, received monthly early indicator reporting for review. The AE reviewed summaries of the quarterly early indicator reporting.

The EoR conducted four field inspections and data reviews and provided a detailed 2024 annual performance review with input from the RTFE, site engineers, and operators.

In addition, FCX's TST, led by a third-party reviewer, completed an annual inspection and data review of the Climax TSFs in July 2024. For context, the TST began its regular inspections at Climax in 2005. The next annual inspection is planned for 2025.

The ITRB for the Climax TSFs is engaged in periodic reviews over the TSF lifecycle. The ITRB initially was engaged in 2014 and has had multiple quadrennial and update review meetings with the site. Specifically, the ITRB for the Climax TSFs completed the most recent update meeting in June 2024. The next ITRB quadrennial review is planned for 2026.

The most recent Tailings Management System Implementation Assessment was completed in 2023, with the next assessment planned for the second half of 2025.

A summary of material findings from these inspections and reviews is presented in the following section.

2.6 Material Findings from TSF Safety Performance Reviews of the Climax TSFs and Mitigations to Reach ALARP

As described in Section 1.4, FCX and its subsidiaries conduct multifaceted reviews of TSF safety. Reviews consider annual performance data, observations, and documentation and provide conclusions on the overall performance of the TSF. Reviews may result in TSF Safety Performance material³ findings as defined in Section 1.4.

There was one material finding identified for the Climax TSFs received during the 2024 review process, as discussed below in Table 4:

Table 4. Summary of Material Findings, Recommendations, and Associated Climax Action Plans as of December 31, 2024

TSF	Recommendations to address Material Findings	Action Plan	Status
All TSFs	Probable Maximum Precipitation (PMP) was re-evaluated to reflect updates to State of Colorado Guidelines, resulting in an increase in a PMP design event.	Update operational water management criteria to reflect the increased PMP design event.	Complete

The Climax TSFs met the design intent and performed within expectations in 2024 based on the multifaceted dam safety reviews and the annual performance review completed by FCX and the EoR. Several operational and sustaining capital projects were ongoing or completed in 2024 to support continued safe operations.

The risk of the CFM was reviewed following the ALARP principle. A potential risk reduction measure has been identified: evaluate practicability of rerouting the private mine-owned road at the toe of Robinson TSF to reduce exposure of mine personnel travelling in the area.

Currently, the ALARP principle has not been met for Robinson TSF because evaluations are ongoing. The outcomes of the evaluation will determine if the TSF is at ALARP, or whether it is a practicable risk reduction measure which can be implemented. Periodic Climax TSFs risk assessment updates and annual reviews will be performed, as summarized in Section 1.3.

³ As used in this report, the term "material" is based on a different definition of materiality than used in U.S. federal securities laws and regulations or the disclosure requirements of the Securities and Exchange Commission (SEC). Please refer to Cautionary Statement on Page 19 of this report.

2.7 Material Findings of Annual Performance Review of Environmental and Social Monitoring Programs

Social and environmental monitoring programs were completed and reported per the company and regulatory requirements, as applicable. The Climax TSFs are subject to the Colorado Mined Land Reclamation Act and regulations administered by the Colorado Division of Reclamation, Mining and Safety (DRMS). In 2024, with approval by DRMS, Climax updated its Reclamation Plan to adjust the general strategy from a “wet” cover to a “dry” cover concept and to update the associated conceptual water management strategy. The updated Reclamation Plan was submitted with revised closure cost estimates.

The Social Performance Management System (SPMS) is an internal system with the goal of driving consistent social performance, internal coordination, communication, and accountability across operations and various other functions of the business to support the process of identifying and eliminating, managing or mitigating the actual or potential social impacts of any of our activities. The SPMS monitoring program includes community-related grievances; ongoing engagement, dialogue and feedback with the community; and a social baseline study to characterize the social and economic conditions, including potential vulnerabilities and human rights issues, of the areas proximate to the Climax TSFs to provide the necessary contextual information to inform future decisions about the TSFs for the continued protection of public safety. Further, the SPMS monitoring program includes identification of social risks associated with the Climax TSFs via TSF-specific and site risk register processes. There were no material findings⁴ from the SPMS monitoring program in 2024.

The Environmental Management System (EMS) includes monitoring and management of water, air quality, soil quality, vegetation, and wildlife, as well as waste generated by Climax. There were no material findings⁵ resulting from the EMS monitoring program, no material environmental changes associated with the Climax TSFs, and no material environmental impacts due to events during 2024.

2.8 Confirmation of Adequate Financial Capacity

As stated in [FCX's 2024 Form 10-K filing](#), we have the financial capacity to meet current estimated lifecycle costs, including estimated closure, post-closure and reclamation obligations associated with our TSFs.

⁴ As used in this report, a material social performance finding is identified from social performance monitoring and reviews of aspects related to or impacted by TSFs. Material findings may be caused by a material change in the local social, economic or environmental context (including climate) that would reasonably be expected to have a significant effect on the quality of life or stability of the local community or any change in the business or operation (or its assets, liabilities or capital) that would reasonably be expected to have a significant effect on the nature of the operation and / or its positive or negative effects and impacts on the local community and / or others affected by the project.

⁵ As used in this report, a material environmental finding or material findings resulting from a review of environmental monitoring is information that is identified from environmental monitoring and audits of TSFs that may have a significant consequence to human health or the environment, a significant legal component, or a significant operational impact.

CAUTIONARY STATEMENT


This report contains forward-looking statements. Forward-looking statements are all statements other than statements of historical facts, such as plans, projections, expectations, targets, objectives, strategies, commitments, or goals concerning TSF-related performance, operations, risks, scenarios and projects, and the underlying assumptions and estimated impacts on our business and stakeholders related thereto; our expectations regarding risks, CFMs and credible failure scenarios and consequence classifications; future risk mitigation; our continuing commitment to safe and reliable operations; our commitment to operating our TSFs in conformance with the Tailings Standard; the anticipated benefits of the Tailings Standard, including improved tailings management practices across the industry and reduced risks to people and the environment due to TSF failures; our commitment to ensuring our TSFs meet global best practice standards for safety; our tailings management programs, standards and practices, including with respect to engineering, inspection, and surety; closure or divestment of certain operations or TSFs, including associated costs; improvements in operating procedures and technology innovations relating to tailings management; anticipated tailings production; anticipated productive lives of TSFs; post-closure liabilities; regulatory developments; and our overarching commitment to deliver responsibly produced copper and molybdenum, including plans to implement, validate, and maintain validation of our operating sites under specific frameworks. The words “anticipates,” “may,” “can,” “commitments,” “plans,” “pursues,” “believes,” “efforts,” “estimates,” “expects,” “endeavors,” “seeks,” “goals,” “predicts,” “strategy,” “objectives,” “projects,” “targets,” “intends,” “aspires,” “likely,” “will,” “should,” “could,” “to be,” “potential,” “opportunities,” “assumptions,” “guidance,” “forecasts,” “future,” “initiatives,” and any similar expressions are intended to identify those assertions as forward-looking statements. Goals and targets and expected timing to achieve goals and targets are subject to change without notice due to a number of factors. We caution readers that forward-looking statements are not guarantees of future performance and actual results may differ materially from those anticipated, expected, projected or assumed in the forward-looking statements. Important factors that can cause our actual results to differ materially from those anticipated in the forward-looking statements include, but are not limited to, the factors described under the heading “Risk Factors” in our Annual Report on Form 10-K for the year ended December 31, 2024, filed with the SEC, as updated by our subsequent filings with the SEC, and available on our website at [fcx.com](https://www.fcx.com).

Many of the assumptions upon which our forward-looking statements are based are likely to change after the forward-looking statements are made. Further, we may make changes to our business plans that could affect our results. We undertake no obligation to update any forward-looking statements, which speak only as of the date made, notwithstanding any changes in our assumptions, changes in business plans, actual experience, or other changes.

This report contains statements based on hypothetical scenarios and assumptions, and these statements should not be viewed as representative of current risks or forecasts of expected risks. Any third-party scenarios discussed in this report reflect the modeling assumptions and outputs of their respective authors, and their use or inclusion herein is not an endorsement of their underlying assumptions, likelihood, or probability. While certain matters discussed in this report may be significant and relevant to our investors, any significance should not be read as rising to the level of materiality for purposes of complying with the U.S. federal securities laws and regulations or the disclosure requirements of the SEC. The targets, goals, strategies, and projects described in this report are aspirational; as such, no guarantees or promises are made that these targets, goals, strategies, and projects will be met or successfully executed.

Appendix: Consequence of Failure Classification

Flowchart for Population at Risk (PAR)



Other Metrics

Consequence Classification	Incremental Losses		
	Environmental	Health, Social and Cultural	Infrastructure and Economics
Low	Minimal short-term loss or deterioration of habitat or rare and endangered species.	Minimal effects and disruption of business and livelihoods. No measurable effect on human health. No disruption of heritage, recreation, community or cultural assets.	Low economic losses: area contains limited infrastructure or services. <US\$1,000,000.
Significant	No significant loss or deterioration of habitat. Potential contamination of livestock / fauna water supply with no health effects. Process water has low potential toxicity. Tailings not potentially acid generating and have low neutral leaching potential. Restoration possible within 1 to 5 years.	Significant disruption of business, service or social dislocation. Low likelihood of loss of regional heritage, recreation, community, or cultural assets. Low likelihood of health effects.	Losses to recreational facilities, seasonal workplaces, and infrequently used transportation routes. <US\$10,000,000.
High	Significant loss or deterioration of critical habitat or rare and endangered species. Potential contamination of livestock / fauna water supply with no health effects. Process water moderately toxic. Low potential for acid rock drainage or metal leaching effects of released tailings. Potential area of impact is 10-20 square kilometers. Restoration possible but difficult and could take > 5 years.	500-1,000 people affected by disruption of business, services or social dislocation. Disruption of regional heritage, recreation, community or cultural assets. Potential for short-term human health effects.	High economic losses affecting infrastructure, public transportation, commercial facilities or employment. Moderate relocation / compensation to communities. <US\$100,000,000.
Very High	Major loss or deterioration of critical habitat or rare and endangered species. Process water is highly toxic. High potential for acid rock drainage or metal leaching effects from released tailings. Potential area of impact is >20 square kilometers. Restoration or compensation possible but difficult and requires a long time (5-20 years).	1,000 people affected by disruption of business, services, or social dislocation for more than one year. Significant loss of national heritage, community, or cultural assets. Potential for significant long-term human health effects.	Very high economic losses affecting important infrastructure or services (e.g. a highway, industrial facility, or storage facility for dangerous substances) or employment. High relocation / compensation to communities. <US\$1,000,000,000.
Extreme	Catastrophic loss of critical habitat or rare and endangered species. Process water is highly toxic. Very high potential for acid rock drainage or metal leaching effects from released tailings. Potential area of impact >20 square kilometers. Restoration or compensation in kind impossible or requires a long time (>20 years).	5,000 people affected by disruption of business, services or social dislocation for years. Significant national heritage, community facilities or cultural assets destroyed. Potential for severe and / or long-term human health effects.	Extreme economic losses affecting critical infrastructure or services (e.g. a hospital, major industrial complex, major storage facility for dangerous substances) or employment. Very high relocation / compensation to communities and very high social readjustment costs. >US\$1,000,000,000.

Likelihood Categorization

Failure Likelihood Categories	
Likelihood	Description
Very High	There is direct evidence or substantial indirect evidence to suggest it has initiated or is likely to occur in the near future. The annual failure likelihood is more frequent than 1/1,000.
High	The fundamental condition or defect is known to exist; indirect evidence suggests it is plausible; and key evidence is weighted more heavily toward more likely than less likely. The annual failure likelihood is between 1/1,000 and 1/10,000.
Moderate	The fundamental condition of defect is known to exist; indirect evidence suggests it is plausible; and key evidence is weighted more heavily toward less likely than more likely. The annual failure likelihood is between 1/10,000 and 1/100,000.
Low	The possibility cannot be ruled out, but there is no compelling evidence to suggest it has occurred or that a condition or flaw exists that could lead to initiation. The annual failure likelihood is between 1/100,000 and 1/1,000,000.
Remote	Several events must occur concurrently or in series to cause failure, and most, if not all, have negligible likelihood such that failure likelihood is negligible. The annual failure likelihood is more remote than 1/1,000,000.

US Army Corps of Engineers and US Bureau of Reclamation. Best Practices in Dam and Levee Safety Risk Analysis. Version 4.0, July 2019.

ANNEX 1: Acronym Definitions

AE	Accountable Executive
ALARP	As Low As Reasonably Practicable
CFM	Credible Failure Mode
DRMS	Division of Reclamation, Mining and Safety
EoR	Engineer of Record
EMS	Environmental Management System
EPRP	Emergency Preparedness and Response Plan
ERP	Emergency Response Plan
FCX	Freeport-McMoRan Inc.
ICMM	International Council on Mining and Metals
ITRB	Independent Tailings Review Board
OMS	Operations, Maintenance and Surveillance
RIDM	Risk Informed Decision Making
RTFE	Responsible Tailings Facility Engineer
SPMS	Social Performance Management System
Tailings Standard	Global Industry Standard on Tailings Management
TMS	Tailings Management System
TSF	Tailings Storage Facility
TST	Tailings Stewardship Team

END OF THE DOCUMENT